Etimol DFX 80 CA

Catalog-No. 8055

PCBA-Defluxing

Field of Application

Maintenance cleaning of soldering pallets, condensate traps and soldering equipment machine parts

Customer benefits

Defluxing concentrate for PCBA; low odor; eliminates corrosive and flammable chemicals

Please consider approvals of equiment manufacturer!

Technical Data

Appearance / Consistancy:	Colorless to slightly yellow, clear
Application::	1 part concentrate + 4-5 parts DI-water
Density at 20°C:	0,967 +/- 0,005 g/cm³
pH-value	Alkaline
Boiling point / bioling range:	>100°C
System:	Waterbased (ready-mixed)
Flashpoint:	None (ready-mixed)

Operations temperature:	50-65°C
Reliable cleaning results with:	Flux residues
Shelf life (month)	36
Storage conditions	Ideal in original packaging at 10-25°C
Transportation:	Non-DG
Packaging:	5 L blue plastic can 20 L green plastic can

EMIL OTTO
Flux- und Oberflächentechnik GmbH
D-65346 Eltville – Eltviller Landstr. 22

Tel.: +49 (0)6123 / 70 46 0
Fax: +49 (0)6123 / 70 46 15
E-Mail info@emilotto.de Internet: www.emilotto.de

Application notes:

The waterbased, alkaline cleaning concentrate in mixed 1 part concentrate : 4-5 parts DI water to remove bakend flux residues from PCBA. Usually use is within spray-in-air and ultrasonic cleaning equipment at temperatures inbetween 55-65℃.

Consider approvals of equipment manufacturer!

EMIL OTTO
Flux- und Oberflächentechnik GmbH
D-65346 Eltville – Eltviller Landstr. 22

Tel.: +49 (0)6123 / 70 46 0
Fax: +49 (0)6123 / 70 46 15
E-Mail info@emilotto.de Internet: www.emilotto.de